

Screen Size	15" (381mm) Diagonal
Panel	TFT Active Matrix LCD, Slim Bezel
Pixel Pitch	0.297mm x 0.297mm
Display Area	304.1mm x 228.1mm
Brightness	250cd/m ²
Contrast Ratio	300:1
Response Time	30ms
Viewing Angle	Horizontal: 120°, Vertical: 100°
Compatibility	VESA®, XGA, SVGA, VGA, Macintosh™ Equipped with VGA Port
Scanning Frequency	Horizontal: 30KHz ~ 60KHz, Vertical: 55Hz ~ 75Hz
Pixel Clock	80MHz
Maximum Resolution	1024 x 768 @ 75Hz
Recommended Resolution	1024 x 768 @ 60Hz
Resolutions Supported	720 x 400 @ 70Hz, 640 x 480 @ 60/75Hz, 800 x 600 @ 56/60/72/75Hz, 1024 x 768 @ 60/70/72/75Hz
Color	16.7 million colors by dithering
Signal Input	Video: 0.7Vp-p, RGB Analog
Connectors	RGB Signal: 15-pin D-sub Male (attached) Power: Coax Power Jack Audio: 3.5mm head phone jack
Power Source	DC Input: 12VDC 3A / Power Adapter Input: Universal 100~120VAC, 50/60Hz Power Adapter Output: 12VDC 5A (Max)
Power Consumption	<40 Watts (Max); Power saving <5W
Plug & Play	DDC1/2B
EPA Energy Star®	Yes
User Control	5 button OSD , Stand-by Power switch , Power LED
OSD Function	Brightness, Contrast, Black level, Volume, Clock, Phase, H/V Position, Auto Setup, Audio Adjust, All Reset, OSD Position, Power Saving, Language, Color
Emissions Standard	MPR II
Regulations	UL, CSA, FCC-B,
Audio	1W * 2 Stereo Speakers
Other Features	VESA 75mm Wall Mount Compliant*, Kensington® Security Slot
Base Stand	Tilt: 5° Forward, 20° Backward
Dimensions (WxHxD mm)	Monitor: 367 x 360 x 155, Carton: 445 x 435 x 138 Monitor without base:
Dimensions (WxHxD inches)	Monitor: 14.6 x 14.2 x 6.1, Carton: 17.5 x 17.1 x 5.4
Weight	Net: 5.5 lbs (2.5kg), Gross: 8.5 lbs (3.8kg)
Loading Qty with pallet	20' = pcs.; 40' Std = pcs
Warranty	3 years Parts, 1year LCD panel and Backlight , 1 year Labor
UCP Code	663555007865