


E0500



- **15" (13.9" VIEWABLE)**
- **.28MM DOT PITCH**
- **HIGH RESOLUTION**
- **PLUG & PLAY READY**
- **AUTO SETUP FEATURE**
- **SMALL FOOTPRINT**
- **USB AVAILABLE (E0500U)**

| | |
|--------------------------------------|--|
| CRT SIZE/TYPE | 15" (13.9" viewable), non-glare, anti-static coated, Flat Square Tube (FST) with black matrix Invar shadow mask, low electromagnetic field |
| DOT PITCH | 0.28mm |
| MAX. RESOLUTION (H x V) | 1280 x 1024 Non-interlaced (Addressable) |
| RECOMMENDED RESOLUTION | 800 x 600 @ 85Hz |
| COMPATIBILITY | 1280 x 1024 @ 60Hz, VESA® 1024 x 768 @ 85/75Hz, VESA® 800 x 600 @ 85/75Hz, VESA® 640 x 480 @ 85/75Hz, XGA/2, XGA/IBM 8514/A, Super VGA, VGA, Macintosh™*, SPARCStation™*, and more |
| PLUG & PLAY COMPATIBILITY | VESA® DDC2B |
| VERTICAL SCAN RANGE | Auto-synchronizing 50-120Hz |
| HORIZONTAL SCAN RANGE | Auto-synchronizing 30-70KHz |
| MAXIMUM DOT CLOCK | 108MHz (-3 db) nominal |
| DISPLAY AREA (H x V)** | Default: 10.4" x 7.7" (265mm x 195mm) Overscan: 11.2" x 8.4" (284mm x 214mm) |
| INPUT SIGNAL | VIDEO: 0.7 Vp-p/75Ω SYNC: Separate and Composite TTL Level |
| INPUT CONNECTOR/CABLE | 15 pin mini D-sub, 6 ft. (1.8m) captive cable |
| USER CONTROLS | Front: Power, Auto Setup, OSD controls PreVu™ OSD: Contrast, Brightness, Horizontal Position, Horizontal Size, Vertical Position, Vertical Size, Trapezoid, Parallelogram, Pincushion, Pin-Balance, Rotate, Coloright™ Controls, Language Select (English, French, German, Spanish, Italian), OSD Position, Degauss |
| POWER SUPPLY | 100-240Vac 50/60Hz, Auto-switching NUTEK®, VESA® DPMS™ and EPA Energy Star™ Compliant On: <85W; Standby: <40W; Suspend: <15W; Active Off: 8W |
| TILT AND SWIVEL BASE | Removable Base Range: Tilt: 17°; Swivel: 120° |
| DIMENSIONS (W x H x D) | 14.4" x 14.8" x 15.4" (366mm x 376mm x 391mm) |
| WEIGHT | Net: 26.2 lb. (11.9kg) Gross: 31.5 lb. (14.3kg) |
| CERTIFICATION | UL, CSA, TUV/GS, CE, ISO 9241-3, FCC-B, MPR II, DHHS, TCO '92 |
| WARRANTY | 3 years on parts, 3 years on CRT, 3 years on labor |

©1997 Princeton Graphic Systems. All brand names, trademarks, or registered trademarks are the property of their respective owners. Specifications and bezel design subject to change without prior notice. For detailed specifications, latest compatibility and comparison charts, please contact the Princeton Graphic Systems Customer Support Department. * With optional adapter. ** Actual resolution and active display area will depend on timing signal. 21/14FR1501000 Rev00 DC000844



Designed for

 Microsoft
 Windows 95



2801 South Yale Street • Santa Ana, CA 92704
 Tel: 800/747-6249 • 714/751-8405 • Fax: 714/751-5736
 PGS Facts: 714/751-0168 • Internet: www.prgr.com

PRINCETON®
 GRAPHIC SYSTEMS