

Model: SL70

Part No.: 14AP1712A50



UPC Code: 663555 007872

Product Specification

Panel Size/Type	17" TFT Active Matrix LCD, anti-glare and hard coated (3H)
Pixel Dimension	0.264mm x 0.264mm
Native/Optimum Resolution	1280 x 1024
Maximum Resolution	1280 x 1024
Response Time	16ms (typical)
Contrast Ratio	450:1 (typical)
Brightness	260 cd/m ² (typical)
Viewing Angles @Contrast Ratio_≥ 10	Horizontal : ± 70° = 140° Vertical : up 70°, down 70°
Display Colors	16.7 million Color by dithering, 6 bits per primary color
Active Display Area (h x v)	13.31" x 10.65" (337.92mm x 270.34mm)
Analog Input	Video : 0.7 Vpp/75 Ohm Sync. : Separate and Composite TTL Level, Horizontal Frequency : 30 ~ 83 kHz Vertical Frequency : 50 ~ 75 Hz,
Compatibility	Analog : VESA [®] 1280x1024 @75/60Hz , VESA [®] 1024x768 75/70/60Hz, VESA [®] 800x600 @75/72/60/56Hz, VESA [®] 640x480 @75/72/60Hz, Super VGA, VGA, Macintosh [™] 832x624 @75Hz, Power Mac [™] and more
External Connectors	Analog Input : 15-pin mini D-sub x 1 Power : AC in
Cables	One 5 ft (1.8 m) detachable 15-pin mini D-sub cable
Plug & Play	VESA [®] DDC 2B
User Controls and Indicators	User Control : seven button/ control for power and OSD, power LED : Auto Setup, Brightness, Contrast, Display (H-Position, V-Position), Color Temperature PreVu [™] OSD (9300K, 6500K, User), Tracking (Clock/Phase), OSD Display (H. Position, V. Position), Language, Source (Analog, Digital)
Base Stand	Tilt : 5° down, 30° up
Security	Kensington [®] Security Slot
Dimension (w x h x d) Panel: Box:	16.12" x 16.41" x 8.11" (409.4mm x 416.8mm x 206.1mm) – including the base 19.0" x 20.6" x 10.5" (482.6mm x 521mm x 266.7mm)
Weight	Net : lbs. (..... kg) Gross : lbs. kg)
Power Supply (AC/DC Adapter)	Input : 90~264V _{AC} , 60/50Hz, universal
Power Consumption	On: <40W; Active Off: <3W
Power Management	EPA Energy Star [®] compliant
Agency Approvals	FCC-B, UL, cUL
Environmental Conditions	Operating Temperature : 41°F to 95°F (5°C to 35°C) Storage Temperature : -4°F to 131°F (-20°C to 55°C) Operating Humidity : 20 to 80% (no condensation) Storage Humidity : 10 to 90% (no condensation) Operating Altitude : 10,000 ft. Storage Altitude : 30,000 ft.

Product Design & Specifications are subject to change without notice