

**Model: SL90****Part No.: 14MP1904A50****UPC Code: 663555 007889****Product Specification**

<b>Panel Size/Type</b>	19" TFT Active Matrix LCD, anti-glare and hard coated (3H)
<b>Pixel Dimension</b>	0.294mm x 0.294mm
<b>Native/Optimum Resolution</b>	1280 x 1024
<b>Maximum Resolution</b>	1280 x 1024
<b>Response Time</b>	25ms (typical)
<b>Contrast Ratio</b>	600:1 (typical)
<b>Brightness</b>	250 cd/m <sup>2</sup> (typical)
<b>Viewing Angles @Contrast Ratio<sub>≥</sub> 10</b>	Horizontal : ± 85° = 170° Vertical : up 85°, down 85°
<b>Display Colors</b>	16.7 million True Color, 8bits per primary color
<b>Active Display Area (h x v)</b>	14.8" x 11.86" (376.3mm x 301mm)
<b>Digital Input</b>	Digital Visual Interface (DVI)
<b>Analog Input</b>	Video : 0.7 Vpp/75 Ohm Sync. : Separate and Composite TTL Level, Composite Sync on green Horizontal Frequency : 30 ~ 83 kHz Vertical Frequency : 50 ~ 75 Hz,
<b>Compatibility</b>	Digital : DVI , up to 1280 x 1024 resolution  VESA <sup>®</sup> DFP compatible with adapter, Power Mac <sup>™</sup> compatible with ADC adapter  Analog : VESA <sup>®</sup> 1280x1024 @75/60Hz , VESA <sup>®</sup> 1024x768 75/70/60Hz, VESA <sup>®</sup> 800x600 @75/72/60/56Hz, VESA <sup>®</sup> 640x480 @75/72/60Hz, Super VGA, VGA, Macintosh <sup>™</sup> 832x624 @75Hz, Power Mac <sup>™</sup> and more
<b>External Connectors</b>	Digital Input : DVI-D x 1 Analog Input : 15-pin mini D-sub x 1 Power : AC in
<b>Cables</b>	One 5 ft (1.8 m) detachable 15-pin mini D-sub cable One 5 ft (1.8 m) detachable DVI cable
<b>Plug &amp; Play</b>	VESA <sup>®</sup> DDC 2B
<b>User Controls and Indicators</b>	User Control : seven button/ control for power and OSD, power LED : Auto Setup, Brightness, Contrast, Display (H-Position, V-Position), Color Temperature PreVu <sup>™</sup> OSD (9300K, 6500K, User), Tracking ( Clock/Phase), OSD Display (H. Position, V. Position), Language, Source (Analog, Digital)
<b>Base Stand</b>	Tilt : 5° down, 30° up
<b>Security</b>	Kensington <sup>®</sup> Security Slot
<b>Dimension (w x h x d) Panel: Box:</b>	17.58" x 17.67" x 8.12" (446.2mm x 448.9mm x 206.251mm) – including the base 20.6" x 20.6" x 10.7" (524mm x 524mm x 272mm)
<b>Weight</b>	Net : 16.4 lbs. (7.5 kg) Gross : 21 lbs. (9.5 kg)
<b>Power Supply (AC/DC Adapter)</b>	Input : 90~264V <sub>AC</sub> , 60/50Hz, universal
<b>Power Consumption</b>	On: <50W; Active Off: <2W
<b>Power Management</b>	EPA Energy Star <sup>®</sup> compliant
<b>Agency Approvals</b>	FCC-B, UL, cUL
<b>Environmental Conditions</b>	Operating Temperature : 41°F to 95°F (5°C to 35°C) Storage Temperature : -4°F to 131°F (-20°C to 55°C) Operating Humidity : 20 to 80% (no condensation) Storage Humidity : 10 to 90% (no condensation) Operating Altitude : 10,000 ft. Storage Altitude : 30,000 ft.

Product Design &amp; Specifications are subject to change without notice