

Model: VL1715

Part No.: 14AP1711A00



UPC Code: 663555 007896

Product Specification

Panel Size/Type	17.0" Color TFT Active Matrix LCD. Anti-static and hard coated
Pixel Dimension	0.264mm x 0.264mm
Native/Optimum Resolution	1280 x 1024
Maximum Resolution	1280 x 1024
Response Time	25ms (typical)
Contrast Ratio	450:1 (minimum)
Brightness	300 cd/m ² (typical)
Viewing Angles (Contrast Ratio ≥ 10)	Horizontal : ± 75°(typical) = 150° Vertical : 65° to 65°(Up/Down typical)
Display Colors	16.7 million True Color (24-bit)
Active Display Area (h x v)	13.3" x 10.6" (337.920mm x 270.336mm)
Horizontal Frequency	30 ~ 80 kHz
Vertical Frequency	50 ~ 75 Hz
Input Signal	Video : Analog 0.7 Vpp/75 Ω Sync. : TTL level, positive/negative, separate sync
Compatibility	VESA® 1280x1024 @75/60Hz, VESA® 1152x864 @75Hz, VESA® 1024x768 @75/70/60Hz, VESA® 800x600 @75/72/60/56Hz, VESA® 640x480 @75/72/60Hz, Super VGA, VGA, Power Macintosh™ and more
Input Connector/Cables	One 6 ft (1.8m) attached 15-pin D-sub cable
Plug & Play	VESA® DDC 2B
User Controls and Indicators	User Control : 4 button control for OSD, power button, power LED PreVu™ OSD : Auto Adjust, Brightness, Contrast, Color Adjust (9300K, 6500K, 5400K, User), Information, Image Adjust (H-Position/V-Position Sharpness, Fine Tune), Setup Menu (Language, Resolution Notify, OSD Function), Memory Recall , Audio Menu,
Base Stand	Tilt : 0°down, +90° up
Wall/Arm Mount Kensington lock	VESA® FPMPTM compliant 100mm x 100mm wall/arm mounting interface yes
Dimension (w x h x d)	Unit : 14.7" x 15.5" x 8.1" (374mm x 393mm x 207mm) – including the base Unit : 14.7" x 13.4" x 2.8" (374mm x 340mm x 70mm) – without the base Carton : 17.3" x 19.7" x 7.4" (440mm x 500mm x 188mm)
Weight	Net: 11 lbs. (5.0kg) Gross: 14.3lbs. (6.5kg)
Power Supply (AC/DC Adapter)	Input: 100~240V _{AC} , 1.4A~0.7A, 60/50Hz, universal Output: 12V _{DC} , 4.6A
Power Consumption	On: <45W; Off: <2W
Power Management	EPA Energy Star® compliant
Agency Approvals	FCC-B, CSA (CUL), UL1950, CE,
Audio	1W x 2 Stereo Speakers
Environmental Conditions	Operating Temperature : : 32°F to 104°F (0°C to 40°C) Storage Temperature : : -4°F to 140°F (-20°C to 60°C) Operating Humidity : : 10 to 90% (no condensation) Storage Humidity : : 10 to 90% (no condensation) Operating Altitude : : 12,000 ft. Storage Altitude : : 40,000 ft.