

Screen Size	19" (480mm) Diagonal
Panel	TFT Active Matrix LCD, Slim Bezel
Pixel Pitch	0.294mm x 0.294mm
Display Area	376.32 mm x 301.056mm
Brightness	250 cd/m ² (typical)
Contrast Ratio	700:1 (typical)
Response Time	25ms
Viewing Angle	Horizontal: 170°, Vertical: 170°
Compatibility	VESA®, XGA, SVGA, VGA, Macintosh™ Equipped with VGA Port
Scanning Frequency	Horizontal: 24KHz ~ 83KHz, Vertical: 55Hz ~ 76Hz
Maximum Resolution	1280 x 1024 @ 75Hz
Recommended Resolution	1280 x 1024 @ 60Hz
Resolutions Supported	720 x 400 @ 70Hz, 640 x 480 @ 60/70/72/75Hz, 800 x 600 @ 56/60/72/75Hz, 1024 x 768 @ 60/70/75Hz, 1280 x 1024 @ 60/70/75Hz
Color	16 million colors
Signal Input	Video: 0.7Vp-p, RGB Analog, H/V Separate sync, H/V Composite sync Digital RGB DVI Ver 1.0 Sync. On Green 1.0 Vp-p
Connectors	RGB Signal: 15-pin D-sub x 1 Digital DVI-D 24 pin Power: Coax Power Jack DC Input: 12VDC 4A
Power Source	Power Adapter Input: Universal 100~240VAC, 50/60Hz Power Adapter Output: 12VDC 4A (Max)
Power Consumption	<45 Watts (Max); Power saving <3W
Plug & Play	DDC1/2B
EPA Energy Star®	Yes
User Control	4 button OSD , Power switch , Power LED
OSD Function	Brightness, Contrast, Black level, Clock, Phase, H/V Position, Auto Setup, All Reset, OSD Position, Power Saving, Language, Color
Emissions Standard	MPR II
Regulations	UL, CSA, FCC-B,
Audio	1W x 2 Stereo Speakers
Other Features	VESA 75 mm Wall Mount Compliant*,
Base Stand	Tilt: 5° Forward, 20° Backward
Dimensions (WxHxD mm)	Monitor: 437 x 470 x 195, Carton: 540 x 530 x 255, Monitor without base: 437 x 405 x 85
Dimensions (WxHxD inches)	Monitor: 17.21 x 18.51 x 7.68, Carton: 21.27 x 20.88 x 10.04
Weight	Net: 13 lbs (5.9kg), Gross: 17.41 lbs (7.9kg)
Loading Qty with pallet	20' = pcs.; 40' Std = pcs
Warranty	1 years Parts, 1 year LCD panel and Backlight , 1 year Labor
UCP Code	663555007773